

Legs® Wallboard Anchor

PRODUCT DESCRIPTION

The Legs anchor is a one piece drive type anchor designed for use in hollow gypsum wallboard for light to medium duty loads. It is made from heat treated carbon steel which is zinc coated using a special plating process and can be used with No. 6 or No. 8 screws.

The Legs anchor is a fast, easy to use expansion anchor designed for use in wallboard. As the screw enters the anchor, it engages the pre-formed tabs in each leg causing them to expand outwards into the base material. Removal of the anchor, if required, is easy. Once removed, the anchor leaves a small slit in the wallboard versus the gaping holes left with other types of hollow wall anchors.


FEATURES AND BENEFITS

- Fast and easy to use
- Leaves small "slit" in wallboard, versus larger holes left with other wall anchors


MATERIAL AND INSTALLATION SPECIFICATIONS

Anchor Component	Component Material
Anchor Body	Heat Treated Spring Steel


Place the tip of the anchor against the face of the wallboard and tap in with a hammer or back of a screwdriver until the flange is seated flush against the wallboard



Locate the fixture and insert a No. 6 or No. 8 sheet metal screw through the fixture hole into the installed anchor. Tighten the screw until the fixture is securely seated against the base material and the anchor is fully expanded.



To Remove – Remove the screw and the fixture, then insert the screw into the anchor one turn. Pull on the screw to slide the anchor out of the slit in the face of the wallboard.



SECTION CONTENTS Page No.

General Information.....	282
Material and Installation Specifications.....	282
Performance Data.....	282
Ordering Information.....	282



Legs

ANCHOR MATERIAL

Carbon Steel

ANCHOR SIZE RANGE (TYP.)

Use with No. 6 or No. 8 screws

SUITABLE BASE MATERIALS

Wallboard

WALL ANCHORS

PERFORMANCE DATA

Ultimate and Allowable Load Capacities for Legs in Wallboard¹

Load	3/8" Wallboard		1/2" Wallboard		5/8" Wallboard		3/4" Wallboard	
	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
Ultimate Loads	60 (0.3)	85 (0.4)	70 (0.3)	115 (0.5)	95 (0.4)	165 (0.7)	100 (0.5)	170 (0.8)
Allowable Loads	15 (0.1)	20 (0.1)	20 (0.1)	30 (0.1)	25 (0.1)	40 (0.2)	25 (0.1)	45 (0.2)

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0

ORDERING INFORMATION

Legs Drywall Anchor

Cat. No.	Description	Standard Box	Standard Carton	Wt./100
2336	Legs Wallboard Anchor	100	1,000	3/4
2335	Legs Anchor, No. 8 x 1" Screw	100	1,000	1 3/4



Master Pack

Cat. No.	Description	Standard Box	Standard Carton	Wt./100
2338	Legs Wallboard Anchor	–	5,000	3/4
2337	Legs Wallboard Anchor	–	5,000	3/4

Legs Anchor Kit

Cat. No.	Description	Standard Box	Standard Carton	Wt./100
2360	Legs Wallboard Anchor Kit 50 Anchors and No. 8 x 1" Screws	1	10	9