



# SPECIFICATION SHEET

## 155-0-11



### NOVAX RUBBER INSULATING GLOVES

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

### APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

### MAX USE VOLTAGE

CLASS 0	SC V rms	DC V
	1,000	1,500

10
**NOVAX™ by G.B. INDUSTRIES**  
 ANSI / ASTM CLASS 0    MADE IN MALAYSIA    D120 TYPE I  
**MAX USE VOLT 1000V AC**



### TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Black/Orange
CUFF STYLE	Rolled
SIZES	8-11
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	(147): 16.9" x 16.9" x 12.8" (150 / 155): 14.4" x 12.6" x 18.9"
CASE WEIGHT	11.0 lbs / 5.0 kg
COO	Malaysia

### BARCODES

ITEM	PAIR	CASE
155-0-11/8	01616314059338	02616314059337
155-0-11/9	01616314059345	02616314059344
155-0-11/10	01616314059352	02616314059351
155-0-11/11	01616314059369	02616314059368

### DIMENSIONS (in/cm)

	8	9	10	11
<b>A</b>	28.0 / 11.0	28.0 / 11.0	28.0 / 11.0	28.0 / 11.0
<b>B</b>	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5

Max Thickness: 1.02mm\*

